

ELECRAFT K3 OWNER'S MANUAL & SOFTWARE ERRATA

Rev. D4-1, May 11, 2009

K3 Utility PC/Mac Program (revision 1.2.3.18)

- **Added message buffer editor for CW and CW-to-Data modes** (*Configuration* tab); supports CW half-space and insertion of the "IM" stop character into a CW messages for use with RTTY and PSK31.
- **Added automatic transmit gain calibration procedure** (*Configuration* tab); much easier than the manual calibration procedure shown in the owner's manual (rev. D1, pg. 48)
- **Added programmable "sign-on banner"** that scrolls across the VFO B display at power-on; useful for customizing your K3 by displaying your call, rig serial number, etc. (*Configuration* tab)

K3 Firmware (MCU revision 3.13, DSP revision 2.16)

Omissions: The features below are described in the Owner's manual but not yet available in firmware.

- Synchronous AM receive
- Separate TX EQ for ESSB
- "Method 3" compensation for the high-stability TCXO option, model KTCXO3-1. **Note:** Even without this compensation step, the KTCXO3-1 typically exhibits stability of +/- 0.5 PPM over 0-50 C.

Additions: The features below are present in K3 firmware but not yet described in the manual; refer to details in the firmware release notes for additional details.

None.

See http://www.elecraft.com/K3/k3_software.htm for firmware release notes and update instructions.

Owner's Manual

None.